

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	Holzwerk Gebr. Schneider GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-HWS-20240044-IBA2-EN
Issue date	04.04.2024
Valid to	03.04.2029

best wood BSH
Holzwerk Gebr. Schneider GmbH

www.ibu-epd.com | <https://epd-online.com>



1. General Information

Holzwerk Gebr. Schneider GmbH

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-HWS-20240044-IBA2-EN

This declaration is based on the product category rules:

Solid wood products, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

04.04.2024

Valid to

03.04.2029



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

best wood BSH

Owner of the declaration

Holzwerk Gebr. Schneider GmbH
Kappel 28
88436 Eberhardzell
Germany

Declared product / declared unit

1 m³ Brettschichtholz best wood BSH

Scope:

Die vorliegende Umwelt-Produktdeklaration bezieht sich auf 1 m³ best wood BSH, welches von der Firma Holzwerk Gebr. Schneider GmbH am Standort Eberhardzell (Deutschland) hergestellt wird. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.


The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR

Independent verification of the declaration and data according to ISO 14025:2011

internally externally



Matthias Klingler,
(Independent verifier)

2. Product

2.1 Product description/Product definition

Best wood glued laminated timber (GLULAM) is a solid, rod-shaped timber component made of at least three fiber-parallel board lamellas glued together. The product is characterised by its high dimensional stability and load-bearing capacity. best wood GLULAM is available as a standard product as well as in special dimensions. best wood GLULAM can also be used as a flat ceiling element in 'visible quality (SI)' and 'non-visible quality (NSI)'. The best wood GLULAM is manufactured in accordance with EN 14080. Regulation (EU) No. 305/2011 (CPR) applies to the placing on the market of the product in the EU/EFTA (with the exception of Switzerland). The product requires a declaration of performance in accordance with DIN EN 14080:2013-09 - Timber structures - Glued laminated timber and laminated beams- Requirements and CE marking.

The respective national regulations apply for use.

2.2 Application

The product best wood GLULAM is used in the structural area of modern timber construction. The areas of application include residential, industrial and bridge construction. It can be used in utilisation classes 1 and 2 in accordance with EN 1995-1-1.

2.3 Technical Data

The technical construction data shown below is valid for the product best wood GLULAM mat as delivered. Depending on the cross-sectional structure (number of layers, layer thickness) and the load position of the best wood GLULAM, the physical building properties such as component resistance or fire resistance vary. Strength classes from GL 24 are available for dimensioning in accordance with EN 1995-1-1 and these are designed in a homogeneous structure.

Technical construction data

Name	Value	Unit
Wood types by trade names according to EN 1912	Fichte	-
Wood moisture according to EN 13183-1	< 15	%
Use of wood preservatives (the test rating of the wood preservative in accordance with DIN 68800-3 must be specified)	not available	-
Compressive strength parallel according to EN 1995	≥ 24	N/mm ²
Compressive strength rectangular according to EN 1995	2.5	N/mm ²
Tensile strength parallel according to EN 1995	≥ 19,2	N/mm ²
Tensile strength rectangular according to EN 1995	0.5	N/mm ²
Modulus of elasticity according to EN 1995	≥ 11500	N/mm ²
Shear strength according to EN 1995	3.5	N/mm ²
Shear modulus according to EN 1995	650	N/mm ²
Dimensional deviation (length)	±5	mm
Dimensional deviation (width)	±2	mm
Dimensional deviation (height)	±2	mm
Gross density according to EN 338 or DIN 1052, non-load-bearing components: according to DIN 68364	430	kg/m ³
Surface quality (possible forms are to be specified)	Visible quality, non-visible quality	-
Thermal conductivity according to EN 12664	0.13	W/(mK)
Specific heat capacity according to EN 12664	1.6	kJ/kgK
Water vapour diffusion resistance factor according to EN ISO 12572	20 (moist) 50 (dry)	-

Performance values of the product according to the declaration of performance in relation to its essential characteristics in accordance with DIN EN 14080:2013-09 - Timber structures - Glued laminated timber and laminated beams-Requirements.

2.4 Delivery status

Widths from 40 mm to 280 mm
 Heights from 80 mm to 1000 mm
 Lengths of 2.30-18 m

Delivery is made according to batch size 1. The product must be stored dry and under cover.

2.5 Base materials/Ancillary materials

Composition by mass

Name	Value	Unit
Coniferous wood	approx. 90,5	%
Water	approx. 9,0	%
Glue	approx. 0,5	%

The softwood used is predominantly spruce. The adhesives used are based on polyurethane (PUR) and are formaldehyde-free

The product/at least one part of the product contains substances on the ECHA Candidate List of Substances of Very

High Concern (SVHC) (date 14/03/2023) above 0.1 mass %:
no.

The product/at least one sub-product contains other CMR substances of category 1A or 1B that are not on the ECHA candidate list, above 0.1% by mass in at least one sub-product:
no.

Biocidal products have been added to this construction product or it has been treated with biocidal products (it is therefore a treated product within the meaning of the Biocidal Products Regulation (EU) No. 528/2012): **no.**

2.6 Manufacture

In production, technically dried wood slats with a moisture content of 8-15% are used, which are sorted according to strength and pressed into endless slats using a finger joint. These slats are cut to an individual length during the production process, then levelled and pressed into GLULAM wooden beams. Each GLULAM product is planned to order size at the end. When used as a ceiling element, the components are additionally profiled and processed by a CNC-controlled joinery system as required. If required, the surface of the ceiling elements can be finished before packaging.

2.7 Environment and health during manufacturing

The legal regulations regarding environmental and health protection during the manufacturing process are complied with. Legal limits are undercut. In addition, employees are offered numerous health-promoting measures outside of the production process.

The SCHNEIDER Group operates a certified energy management system in accordance with *ISO 50001*.

2.8 Product processing/Installation

The product best wood GLULAM can be processed with the usual tools suitable for solid wood processing. Instructions on occupational safety must be observed during processing/installation.

2.9 Packaging

The products are wrapped in a polyethylene (PE) film to protect them from moisture and UV radiation. After use, the packaging material can be recycled or used to generate energy.

2.10 Condition of use

If used as intended, no material changes in composition are to be expected during the use phase. During use, around 194.5 kg of carbon is bound in the product. This corresponds to approx. 713.1 kg of CO₂ when fully oxidised.

2.11 Environment and health during use

When used as intended, no negative effects on the environment or health are to be expected.

2.12 Reference service life

When installed professionally and used as intended, no premature end to the durability of the GLULAM is known or to be expected. The average service life of the product is therefore of the same order of magnitude as the service life of the building. Under Central European climatic conditions, a conservatively estimated service life of 100 years can be assumed.

Influences on product ageing when used in accordance with the rules of technology are not known or expected.

2.13 Extraordinary effects

Fire

The fire behavior of the declared product is defined as follows:

Fire protection

Name	Value
Building material class	D
Burning droplets	d0
Smoke gas development	s2

Water

In the event of unforeseen exposure of the product to water, e.g. flooding, no substances hazardous to water are washed out.

Mechanical destruction

Best wood GLULAM has a typical fracture pattern for solid wood. No negative effects on the environment are to be expected in the event of unforeseen mechanical destruction.

2.14 Re-use phase

After selective dismantling, the product can generally be reused or recycled without any problems. Alternatively, the material can also be thermally recycled for energy recovery.

2.15 Disposal

In cases where the GLULAM is not recycled, it can be disposed of by means of thermal treatment. Landfilling of waste wood is not permitted.

Waste code according to the European Waste Catalogue (*EWC waste code number*): 170201.

2.16 Further information

Further information and documents such as technical data sheets, certificates etc. are available at www.schneider-holz.com.

3. LCA: Calculation rules

3.1 Declared Unit

The declared unit for this Environmental Product Declaration is defined as 1 m³ in accordance with the specifications of the corresponding PCR: Solid wood product. The gross density of the product in question is 430 kg/m³ with a delivery moisture content of 10 %.

Declared unit and mass reference

Name	Value	Unit
Declared unit	1	m ³
Gross density	430	kg/m ³
Wood moisture at delivery	10	%

Specific data was used for the PUR adhesives used in the modelling.

3.2 System boundary

This EPD is a cradle-to-grave analysis and module D, it includes the following life cycle phases:

A1-A3 | Production stage

The production stage includes the manufacture of all components of the declared product (wooden slats and adhesives) as well as the packaging, including the respective upstream chains up to the extraction of raw materials. The transportation of the components and packaging materials to the production site is also taken into account. All expenses for

the production of the glulam elements are taken into account within the factory limits.

A4-A5 | Construction stage

This stage includes the transportation of the GLULAM elements to the construction site (A4) as well as the expenses for installation in the building (A5). Furthermore the disposal of packaging waste is taken into account here.

B1-B7 | Utilisation stage

This utilisation stage deals with the phase of the product. However, if used properly, no environmentally relevant processes occur during the period of use.

C1-C4 | Disposal stage

The disposal stage includes dismantling (C1), which in this case was assumed to be a manual process with negligible environmental impacts. Furthermore, the transportation of the dismantled product, which is therefore waste, to the waste treatment plant (C2) and its thermal recovery (C3) are also taken into account. In this case, no environmentally relevant processes are included in C4.

D | Advantages and drawbacks outside the system boundary

The advantages of thermal recycling of offcuts and packaging waste (from A5) and of the product itself (from C3) are considered here.

3.3 Estimates and assumptions

The specified density of the declared product corresponds to that of the wood used. The change caused by the adhesive was categorised as very small and therefore not taken into account for the balancing.

3.4 Cut-off criteria

All inputs and outputs for which data is available and which are expected to make a significant contribution are included in the LCA model. Only data with a contribution of less than 1% was cut off. The omission of this data is justified by the insignificance of the expected impact. This means that no processes, materials or emissions were neglected that are expected to make a significant contribution to the environmental impact of the products under consideration. It can be assumed that the data was recorded in full and that the total sum of the neglected input flows does not exceed 5% of the energy and mass input. Expenses for machinery and infrastructure were not taken into account.

3.5 Background data

The modelling was carried out using Umberto LCA+ software on the basis of GaBi databases integrated into it. Background data comes from the GaBi Professional database (2021.2) (GaBi A), GaBi Extension database XIIIb: ecoinvent 3.7.1 integrated (2021.2) (GaBi B) and GaBi Extension database XIV: Construction materials (2021.2) (GaBi C).

3.6 Data quality

The data collection followed the principles described in ISO 14044. The foreground production data for 2021 was collected by Holzwerk Gebr. Schneider GmbH using internal company

records.

When selecting the background data, attention was paid to the technological, geographical and time-related representativeness of the data basis.

3.7 Period under review

The foreground production data was collected for the year 2021. All values therefore represent an average over this period.

3.8 Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Germany

3.9 Allocation

General information

The material-inherent properties of the product (biogenic carbon and the primary energy it contains) are allocated according to the physical criterion of mass.

Module A1-A3

The upstream chains of the respective input materials are mapped using generic data sets. Allocation rules in these datasets can generally be found in the respective dataset documentation. The flows/loads from the forest and sawmill associated with the wood lamellas were modelled as standard using economic allocation.

According to the manufacturer, no other (by-) products are created during the manufacture of the declared product, so an allocation is not necessary at this level.

Modules A5 & C3

The thermal recycling of the packaging waste (A5) and the product itself (C3) takes place in a waste incineration plant (WIP). The associated loads are declared in the respective modules. The waste incineration plant is a multi-input process. The respective allocation takes place via the selected GaBi background datasets – details can be found in the respective dataset documentation.

Module D

Packaging waste as well as the declared product itself are thermally recycled. The associated benefits through the substitution of primary energy sources are presented in Module D. The breakdown into electrical and thermal energy can be found in the corresponding documentation of the GaBi dataset.

3.10 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to EN 15804 and the building context, respectively the product-specific characteristics of performance, are taken into account. GaBi background data from GaBi Professional database (2021.2), GaBi Extension database XIIIb: ecoinvent 3.7.1 integrated (2021.2) and GaBi Extension database XIV: Construction materials (2021.2) were used in the modelling.

4. LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

The biogenic carbon in wood was taken into account in A1-A3 as absorption and derecognised at the end of life (C3). Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO2.

Information on the description of the biogenic carbon content at the site gate

Name	Value	Unit
Biogenic carbon content in product	194.5	kg C
Biogenic carbon content in accompanying packaging	-	kg C

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

The following technical information is the basis for the declared modules or can be used for the development of specific scenarios in the context of a building assessment if modules are not declared (MND). Unless otherwise defined, the values in the following tables refer to the declared unit of 1 m²(= 430 kg).

Transportation to construction site (A4)

Name	Value	Unit
Litres of fuel	34.2	l/100km
Transport distance	138	km
Capacity utilisation (including empty runs)	65	%
Gross density of products transported	430	kg/m ³
Capacity utilisation volume factor	1	-

Installation in the building (A5)

Name	Value	Unit
Auxiliary	-	kg
Water consumption	-	m ³
Other resources	-	kg
Electricity consumption	0.048	kWh
Other energy carriers	-	MJ
Material loss	-	kg
Plastic packaging for thermal waste treatment	0,43	kg
Dust in the air	-	kg
VOC in the air	-	kg

End of life (C1–C4)

Name	Value	Unit
Collected separately waste type Altholz	430	kg
Energy recovery	430	kg

A transportation distance of 200 km to the thermal treatment system (with R1 > 65 %) is assumed. The collection rate is set at 100 %.

Reuse, recovery and recycling potential (D), relevant scenario data

Name	Value	Unit
Energyrecovery elec. from A5	2,87	MJ
Energy recovery therm. from A5	5,11	MJ
Energy recovery elec. from C3	1125,03	MJ
Energy recovery therm. from C3	2020,57	MJ

5. LCA: Results

The results for 1 m³ of best wood GLULAM with a bulk density of 430 kg/m³ are shown below.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m³ Brettschichtholz BSH (430 kg/m³)

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	-5.54E+02	4.78E+00	1.39E+00	0	0	0	1.91E+01	7.25E+02	0	-2.56E+02
GWP-fossil	kg CO ₂ eq	1.58E+02	4.74E+00	1.39E+00	0	0	0	1.9E+01	1.15E+01	0	-2.56E+02
GWP-biogenic	kg CO ₂ eq	-7.13E+02	0	0	0	0	0	0	7.13E+02	0	0
GWP-luluc	kg CO ₂ eq	5.53E-01	3.88E-02	1.91E-04	0	0	0	1.57E-01	7.38E-03	0	-1.75E-01
ODP	kg CFC11 eq	2.05E-07	9.38E-16	5.66E-16	0	0	0	3.79E-15	1.02E-13	0	-2.88E-12
AP	mol H ⁺ eq	5.57E-01	5.1E-03	2.76E-04	0	0	0	1.02E-01	1.11E-01	0	-3.31E-01
EP-freshwater	kg P eq	1E-03	1.41E-05	1.22E-07	0	0	0	5.7E-05	1.4E-05	0	-3.3E-04
EP-marine	kg N eq	2.37E-01	1.64E-03	8.69E-05	0	0	0	4.92E-02	3.63E-02	0	-9.45E-02
EP-terrestrial	mol N eq	2.57E+00	1.95E-02	1.27E-03	0	0	0	5.45E-01	5.27E-01	0	-1.01E+00
POCP	kg NMVOC eq	6.93E-01	4.44E-03	2.05E-04	0	0	0	9.56E-02	9.87E-02	0	-2.65E-01
ADPE	kg Sb eq	5.76E-05	4.21E-07	8.89E-09	0	0	0	1.7E-06	1.55E-06	0	-4.21E-05
ADPF	MJ	2.27E+03	6.33E+01	7.63E-01	0	0	0	2.55E+02	1.69E+02	0	-4.43E+03
WDP	m ³ world eq deprived	1.36E+01	4.41E-02	1.27E-01	0	0	0	1.78E-01	8.05E+01	0	-1.91E+01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m³ Brettschichtholz BSH (430 kg/m³)

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C4	D
PERE	MJ	3.59E+02	3.64E+00	2.05E-01	0	0	0	1.47E+01	7.46E+03	0	-9.86E+02
PERM	MJ	7.42E+03	0	0	0	0	0	0	-7.42E+03	0	0
PERT	MJ	7.78E+03	3.64E+00	2.05E-01	0	0	0	1.47E+01	3.28E+01	0	-9.86E+02
PENRE	MJ	2.2E+03	6.35E+01	1.9E+01	0	0	0	2.56E+02	2.23E+02	0	-4.44E+03
PENRM	MJ	7.2E+01	0	-1.83E+01	0	0	0	0	-5.38E+01	0	0
PENRT	MJ	2.27E+03	6.35E+01	7.64E-01	0	0	0	2.56E+02	1.69E+02	0	-4.44E+03
SM	kg	0	0	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0	0
FW	m ³	5.96E-01	4.17E-03	3.08E-03	0	0	0	1.68E-02	1.89E+00	0	-9.6E-01

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m³ Brettschichtholz BSH (430 kg/m³)

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C4	D
HWD	kg	6.11E-07	3.35E-09	1.34E-10	0	0	0	1.35E-08	3.05E-08	0	-9.96E-07
NHWD	kg	1.66E+00	9.96E-03	5.62E-03	0	0	0	4.02E-02	5.59E+00	0	-2.07E+00
RWD	kg	8.11E-02	1.15E-04	6.09E-05	0	0	0	4.65E-04	9.39E-03	0	-3.16E-01
CRU	kg	0	0	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	0	0	0	0
MER	kg	0	0	0	0	0	0	0	0	0	0

EEE	MJ	0	0	2.87E+00	0	0	0	0	1.13E+03	0	0
EET	MJ	0	0	5.11E+00	0	0	0	0	2.02E+03	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:
1 m³ Brettschichtholz BSH (430 kg/m³)**

Parameter	Unit	A1-A3	A4	A5	B1	B2	C1	C2	C3	C4	D
PM	Disease incidence	1.12E-04	3.47E-08	1.53E-09	0	0	0	4E-07	5.55E-07	0	-2.85E-06
IR	kBq U235 eq	7.46E+00	1.68E-02	9.93E-03	0	0	0	6.8E-02	1.49E+00	0	-5.17E+01
ETP-fw	CTUe	1.24E+03	4.69E+01	4.08E-01	0	0	0	1.9E+02	7.31E+01	0	-9.12E+02
HTP-c	CTUh	1.06E-07	9.49E-10	1.66E-11	0	0	0	3.84E-09	4.91E-09	0	-4.21E-08
HTP-nc	CTUh	7.83E-06	4.93E-08	6.37E-10	0	0	0	2.11E-07	1.75E-07	0	-1.66E-06
SQP	SQP	1.24E+05	2.17E+01	2.42E-01	0	0	0	8.78E+01	4.63E+01	0	-6.77E+02

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (carcinogenic); HTP-nc = Potential comparative Toxic Unit for humans (not carcinogenic); SQP = Potential soil quality index

Restriction notice 1 – applies to the indicator 'Potential effect of human exposure to U235'. This impact category mainly addresses the potential effect of low dose ionizing radiation on human health in the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents and occupational exposure, nor to the disposal of radioactive waste in underground facilities. Potential ionizing radiation from soil, radon and some building materials is also not measured by this indicator.

Restriction notice 2 – applies to the indicators: 'Potential for depletion of abiotic resources - non-fossil resources', 'Potential for depletion of abiotic resources - fossil fuels', 'Water depletion potential (user)', 'Potential toxicity comparison unit for ecosystems', 'Potential toxicity comparison unit for humans - carcinogenic effect', 'Potential toxicity comparison unit for humans - non-carcinogenic effect', 'Potential soil quality index'. The results of this environmental impact indicator must be used with caution, as the uncertainties in these results are high or because there is only limited experience with the indicator.

6. LCA: Interpretation

A closer look at the results presented in Chapter 5 shows that the manufacturing phase (A1-A3) has by far the greatest impact in almost all cases. One exception is the GWP-biogenic impact indicator, which is zero over the entire life cycle of the product under consideration. The credits caused in A1–A3 (due to the carbon absorption in the wood fibers used) are offset during disposal (module C3). As these values exceed those of the GWP-fossile, this effect is also visible in the GWP-total, where module C3 therefore also plays a significant role.

A detailed analysis of modules A1-A3 shows that the wood used (including upstream chain) is the central influencing factor

for most indicators. Exceptions to this are EP-freshwater, ADPE, ADPF and WDP, which are also significantly influenced by the production of the adhesive.

Most of the life cycle inventory indicators for the product under consideration are also primarily influenced by module A1-A3. Module C3 plays the largest role for renewable energy consumption (PERE), non-hazardous waste (NHWD) and fresh water consumption (FW). As expected, this module is also the most significant for exported energy (EEE and EET). All other modules consistently play a subordinate role.

7. Requisite evidence

7.1 Formaldehyde

The adhesive system used does not contain formaldehyde. The corresponding verification is therefore not required.

7.2 MDI

The declared product is a cold-bonded load-bearing solid wood product containing moisture-crosslinked single-component polyurethane adhesives. The verification is therefore not required.

7.3 Toxicity of combustion gases

The toxicity of the combustion gases produced when glulam burns correspond to those produced when untreated wood burns.

The following VOC emissions were determined by the Bremer Umweltinstitut [Bremer Environment Institute] - analysis report number: L 6605 FM dated 25/11/2022. The indication 'n.n.' stands for not detectable, the measured value is therefore below the detection limit of 1 µg/m³.

AgBB results overview (28 days [µg/m³])

Name	Value	Unit
TVOC (C6 - C16)	20	µg/m ³
Sum SVOC (C16 - C22)	n.n.	µg/m ³
R (dimensionless)	0.056	-
VOC without NIK	n.n.	µg/m ³
Carcinogenic Substances	n.n.	µg/m ³

AgBB results overview (3 days [µg/m³])

Name	Value	Unit
TVOC (C6 - C16)	126	µg/m ³
Sum SVOC (C16 - C22)	5	µg/m ³
R (dimensionless)	0.165	-
VOC without NIK	4	µg/m ³
Carcinogenic Substances	n.n.	µg/m ³

8. References

Standards

EN 1995-1-1
DIN EN 1995-1-1:2010-12, Eurocode 5: Design of timber

structures - Part 1-1: General - Common rules and rules for buildings (EN 1995-1- 1:2004 + AC:2006 + A1:2008).

EN 13501-1

DIN EN 13501-1:2019-05, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests.

EN 14080

DIN EN 14080:2013-09, Timber structures - Glued laminated timber and glued solid timber - Requirements.

ISO 14025

DIN EN ISO 14025:2011-10, Environmental labels and declarations - Type III environmental declarations -Principles and procedures.

ISO 14040

DIN EN ISO 14040:2021-02, Environmental management - Life cycle assessment - Principles and framework (ISO 14040:2006 + Amd 1:2020).

ISO 14044

DIN EN ISO 14044:2021-02, Environmental management - Life cycle assessment - Requirements and guidelines (ISO 14044:2006 + Amd 1:2017 + Amd 2:2020).

EN 15804

DIN EN 15804:2022-03, Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products.

CEN/TR 15941

CEN/TR 15941:2010-03, Sustainability of construction works - Environmental product declarations - Methodology for selection and use of generic data.

ISO 50001

DIN EN ISO 50001:2018-12, Energy management systems - Requirements with guidance for use.

Further sources**EWC**

European Waste Catalogue according to the Waste Catalogue

Ordinance (AVV) of 10 December 2001 (BGBl. I p. 3379), last amended by Article 1 of the Ordinance of 30 June 2020 (BGBl. I p. 1533).

ECHA Candidate List

List of substances of very high concern for authorisation (published in accordance with Article 59 (10) of the REACH Regulation).

GaBi A

GaBi Professional database (2021.2), Sphera Solutions GmbH, Leinfelden-Echterdingen.

GaBi B

GaBi ext. DB XIIIb - ecoinvent integrated v3.7.1 (2021.2), Sphera Solutions GmbH, Leinfelden-Echterdingen.

GaBi C

Extension database XIV: Construction materials (2021.2), Sphera Solutions GmbH, Leinfelden-Echterdingen.

IBU 2022

General instructions for the EPD program of Institut Bauen und Umwelt e.V., version 2.1, dated 01/10/2022.

PCR Part A

Product category rules for building-related products and services - Part A: Calculation rules for the life cycle assessment and requirements for the project report according to EN 15804+A2:2019, Version 1.3, dated 28/08/2022.

PCR: Solid wood products

PCR guidance texts for building-related products and services - Part B: Requirements for the EPD for solid wood products, version 5, dated 18/07/2023.

Umberto

Umberto LCA + 10.0.3, iPoint-systems GmbH, Reutlingen.

Regulation (EU) No. 305/2011 (CPR)

Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC.



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Österreichisches Institut für Bauen und Ökologie GmbH



Author of the Life Cycle Assessment

IBO - Österreichisches Institut für Bauen und
Ökologie GmbH
Alserbachstraße 5/8
1090 Wien
Austria

+43 13192005
ibo@ibo.at
www.ibo.at



Owner of the Declaration

Holzwerk Gebr. Schneider GmbH
Kappel 28
88436 Eberhardzell
Germany

+49 7355 9320 0
info@schneider-holz.com
www.schneider-holz.com